

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FP160 – 20171124

P1/3

- 1. Unique identification code of the product-type:** FP160
- 2. Intended use/es:** Is a preformed tube, containing a Nullifire FP302 pipe wrap, used to reinstate the fire resistance performance of a wall and floor construction where they have been provided with apertures for the penetration pipes.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026-2 edition 2011 used as European Assessment Document
European Technical Assessment: ETA 17/0391 of 22/10/2017
Technical Assessment Body: CPR Notified Body UL International (UK) Ltd, NB 0843
Notified Body: CPR Notified Body UL International (UK) Ltd, NB 0843

Declared performance/s:

Basic Work Requirement	Performance
Mechanical resistance and stability	
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA17/0391 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	NPD
Water Permeability (ETAG 026-3 Annex C)	NPD
Release of dangerous substances	Use categories: IA3, S/W3 Declaration of manufacturer
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Z ₁

The performance of the product identified above is in conformity with the set of declared performance/s. This

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

P2/3

declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Director Sealants & Coatings



At Wigan on 24 November 2017

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

No. FP160 – 20170630

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

P2/3

CE	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 17 0843-CPR-0379 FP160 – 20171124 www.nullifire.com/FP160/	
EN 1366-3: 2009 ETA 17-0391 ETAG 26, Part 2 Is a preformed tube, containing a Nullifire FP302 pipe wrap, used to reinstate the fire resistance performance of a wall and floor construction where they have been provided with apertures for the penetration pipes.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	See ETA17/0391 Annex A
Hygiene, Health and Environment	
Air Permeability (EN 1026:2000)	NPD
Release of dangerous substances	Use categories: IA3, S/W3 Declaration of manufacturer
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	NPD
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Z ₁