

NTN 042

Product Longevity

Nullifire
Smart Protection

Information

Product - Lifetime of Building (Maximum of 50 Years)

Product - All Nullifire Products

The above products supplied by CPG UK (Nullifire brand) are manufactured to BS EN ISO 9001 accredited quality system. The products either are or become inert after curing and are not subject to reaction with normal construction materials.

These products have been fully fire tested in accordance with the procedures in BS476: Pt 20/21/22 or BS EN 1366-1/3/4 by UKAS approved testing laboratories.

CPG UK warrants the fire performance of these products and that they are "suitable" and "fit for the purpose" in providing a tried and tested fire stopping solution.

This is subject to all products being installed strictly in accordance with our written installation instructions current at the time of supply and maintained in accordance with BS EN ISO 9003:1994 quality standard during the required service life.

Product requiring a protective top-seal are limited to the service life of the top-seal and reapplication dates should be scheduled into building maintenance programs as per the manufacturers instructions.

Any damage, be it physical, water, fire, accidental or wind-load should be rectified immediately as these are life safety products.

All CPG UK products are expected to be included within the buildings routine maintenance plan. A competent person should repair any damage to any CPG UK products immediately, else performance may be seriously impaired. Change in building design or use any beyond our control therefore this area of warranty implication is subject to rigid building specification reviews.

Subject to the above, in our opinion, and in normal internal conditions, we would expect all products to meet the product life period specified above.

Technical Service

Nullifire have a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, on technical advise, please call our technical hub on 01942 251400