

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FB747-60 – 20160225

1. **Unique identification code of the product-type:** Nullifire FB747-60

2. **Intended use/es:** A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. **Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT

5. **System/s of AVCP:** System 1

6b. **European Assessment Document:** ETAG 026, edition 2011 used as European Assessment Document

European Technical Assessment: Warrington Certification Limited issued European Technical Approval – ETA14/0112

Technical Assessment Body: Warrington Certification Limited
Notified Body: 1121, Warrington Certification Limited

7. **Declared performance/s:**

Essential Characteristic	Performance	Harmonised Technical Specification
Safety in Case of Fire		
Reaction to fire	Class F	EN13501-1
Resistance to fire	Up to EI120. Resistance to fire performance & field of application in accordance with BS EN 1366-3: 2009. Classified in accordance with EN 13501-2, as given in Annex C. See ETA14/0112 clause 3.2	BS EN1366-3:2009 EN 13501-2 as given in Annex C
Hygiene, Health and Environment		
Air permeability	See clause 3.3 ETA 14/0112	BS EN 1314-1
Dangerous substances	All dangerous chemical substances are below the classification limits of 67/548/EEC. See ETA14/0112 clause 2.5	
Safety in Use		
Airborne sound insulation	See ETA 14/0112 clause 3.9 – $R_w(C;C_{tr})= 24(-2;-3)$	
Energy, Economy and Heat Retention		
Service & Durability	Z ₁ .	ETAG 026-3

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
M. Liptrot, Business Unit Director Sealants & Coatings
At Wigan on 25th February 2016



DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

CE	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 14 1121-CPR-JA5031 FB747-60 - 20160225 www.nullifire.com/FB747-60/	
EN 1366-3 2009 ETA 14-0112 ETAG 026, Parts 1 and 2 Coated mineral wool board to reinstate the fire resistance performance of rigid and flexible wall constructions where they are penetrated by various cables and metallic pipes.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class F
Resistance to fire	Up to EI120. Resistance to fire performance & field of application in accordance with BS EN 1366-3: 2009. Classified in accordance with EN 13501-2, as given in Annex C. See ETA14/0112 clause 3.2
Hygiene, Health and Environment	
Dangerous Substances	All dangerous chemical substances are below the classification limits of 67/548/EEC. See ETA14/0112 clause 2.5
Air permeability	See clause 3.3 ETA 14/0112
Airborne sound insulation	See ETA 14/0112 clause 3.9 – $R_w(C;C_{tr})= 24(-2;-3)$
Energy, Economy and Heat Retention	
Service & Durability	Z ₁ .
Other	Not applicable/No performance determined