Nullifire Smart Protection

No. FP302 - 20171124

P1/3

- 1. Unique identification code of the product-type: Nullifire FP302 Intustrap
- **2. Intended use/es:** Is a pipe wrap of intumescent material used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration pipes.
- 3. Manufacturer: TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
- 5. System/s of AVCP: System 1
- European Assessment Document: ETAG 026-2 edition 2011 used as European Assessment Document
 European Technical Assessment: Technical Assessment Body: Notified Body:
 ETAG 026-2 edition 2011 used as European Assessment Document
 ETA 17/0391 of 23/10/2017
 CPR Notified Body UL International (UK) Ltd, NB 0843
 CPR Notified Body UL International (UK) Ltd, NB 0843
- 7. Declared performance/s:

Basic Work Requirement	Performance
Mechanical resistance and stability	·
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA17/0391 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	NPD
Water Permeability (ETAG 026-3 Annex C)	NPD
Release of dangerous substances	Use categories: IA3, S/W3
	Declaration of manufacturer
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Z ₁



P2/3

declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: M. Liptrot, Operations Director

At Wigan on 1 July 2020

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.



No. FP302 - 20170630

	(€
TREMCC	D CPG UK Limited,
Coupland Road, Hindle	ey Green, Wigan. WN2 4HT UK
	17
084	43-CPR-0379
	02 – 20171124
	llifire.com/FP302/ 1366-3: 2009
	TA 17-0391
ETA	AG 26, Part 2
performance of wall and floor cons	erial used to reinstate the fire resistance tructions where they have been provided r the penetration pipes.
Essential Characteristic	Performance
Safety	in Case of Fire
Reaction to fire	Class E
Resistance to fire	See ETA17/0391 Annex A
Hygiene, Hea	alth and Environment
Air Permeability (EN 1026:2000)	NPD
Release of dangerous substances	Use categories: IA3, S/W3
	Declaration of manufacturer
Sa	afety in use
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protecti	on against noise
Airborne sound insulation	NPD
Energy, Econo	my and Heat Retention
Thermal properties	NPD
Water vapour permeability	NPD
General aspects	relating to fitness for use
Service & Durability	Z ₁

P2/