

Printing date 14.05.2015

Version number 5

Revision: 14.05.2015

SECTION 1: Identification undertaking	on of the substance/mixture a	and of the company/	
· 1.1 Product identifier			
· Trade name: Nullifire SC900 Re	· Trade name: Nullifire SC900 Repair A		
<ul> <li>MSDS code: W-N-SC900REPA</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.</li> <li>Application of the substance / the mixture Coating compound/ Surface coating/ paint</li> </ul>			
<ul> <li>1.3 Details of the supplier of the Manufacturer/Supplier: tremco illbruck Coatings Ltd Coupland Road, Hindley Green, Tel: +44 (0) 1942251400, Fax: + msds@tremco-illbruck.com</li> </ul>	WIGAN, WN2 4HT		
<ul> <li>Further information obtainable Nullifire</li> <li>Torrington Avenue, Coventry, CV T: +44 (0) 2476855000, F: +44 (0) www.nullifire.com, protect@nullif</li> <li>1.4 Emergency telephone num During office hours tel.: +44 (0) 2 centre.</li> </ul>	/4 9TJ 0) 2476469547 ire.com	ntact your national poisoning	
SECTION 2: Hazards ident	ification		
<ul> <li>• 2.1 Classification of the substation</li> <li>• Classification according to Reg Flam. Liq. 3 H226 Flammable limits</li> </ul>	gulation (EC) No 1272/2008		
<ul> <li>R10: Flammable.</li> <li>Information concerning particular termination for preparations of the guideline for preparations of the classification system:</li> </ul>	ective 67/548/EEC or Directive 1999/45/ ular hazards for human and environmend d due to the calculation procedure of t EU" in the latest valid version.	nt: he "General Classification extended by company and	
<ul> <li>• 2.2 Label elements</li> <li>• Labelling according to Regulat The product is classified and labe</li> <li>• Hazard pictograms</li> </ul>			
GHS02			
· Signal word Warning			
<ul> <li>Hazard statements H226 Flammable liquid and vapo</li> </ul>	pur.		
		(Contd. on page 2)	

Version number 5

Revision: 14.05.2015

Printing date 14.05.2015

#### Trade name: Nullifire SC900 Repair A

(Contd. of page 1)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- · 2.3 Other hazards No further relevant information available.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 1330-20-7	xylene (mix)	5- <10%
EINECS: 215-535-7	Xn R20/21; Xi R38	
Reg.nr.: 01-2119488216-32-xxxx	R10	
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 28553-12-0	di-"isononyl" phthalate	1- <5%
EINECS: 249-079-5	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119430798-28-xxxx		
CAS: 100-41-4	ethylbenzene	1- <5%
EINECS: 202-849-4	Xn R20; F R11	
Reg.nr.: 01-2119489370-35-xxxx	Flam. Liq. 2, H225; Acute Tox. 4, H332	
• Additional information: For the wording of the listed risk phrases refer to section 16.		

# **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:
  - Immediately wash with water and soap and rinse thoroughly.
  - If skin irritation continues, consult a doctor.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

- GB

**Nullifie** Enhancing Fire Protection

(Contd. of page 2)

Version number 5

Revision: 14.05.2015

Trade name: Nullifire SC900 Repair A

Printing date 14.05.2015

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin.
- Information about fire and explosion protection: Flammable liquid and vapour.
   Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles. Provide ventilation for receptacles.
- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Storage temperature:  $+5 \degree$  to  $+25 \degree$
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

**Nullfire** Enhancing Fire Protection

Printing date 14.05.2015

Version number 5

Revision: 14.05.2015

Trade name: Nullifire SC900 Repair A

	(Contd. of page 3)
SEC	TION 8: Exposure controls/personal protection
· 8.1 C	control parameters
· Ingre	edients with limit values that require monitoring at the workplace:
1330	-20-7 xylene (mix)
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
2855	3-12-0 di-"isononyl" phthalate
WEL	Long-term value: 5 mg/m <sup>3</sup>
100-4	41-4 ethylbenzene
WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
· Ingre	edients with biological limit values:
1330	-20-7 xylene (mix)
	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
The I	tional information: ists valid during the making were used as basis. )/2005 Workplace Exposure Limits (2nd edition, 2011)
<ul> <li>Perse</li> <li>Gene</li> <li>Do no</li> <li>Avoid</li> <li>Resp</li> <li>Use of</li> <li>In ca</li> <li>expos</li> <li>Filter</li> </ul>	<pre>xposure controls onal protective equipment: aral protective and hygienic measures: ot breathe spray. ot eat, drink, smoke or sniff while working. d contact with the eyes and skin. iratory protection: only in well-ventilated areas. se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer sure use self-contained respiratory protective device. A/P2 action of hands:</pre>
	Protective gloves
prepa • <b>Mate</b> Nitrile Fluor PVA The s quali	glove material has to be impermeable and resistant to the product/ the substance/ the aration. <b>rial of gloves</b> e rubber, NBR ocarbon rubber (Viton) gloves selection of the suitable gloves does not only depend on the material, but also on further marks of ty and varies from manufacturer to manufacturer. As the product is a preparation of several tances, the resistance of the glove material can not be calculated in advance and has therefore to (Contd. on page 5)

(Contd. on page 5)



Printing date 14.05.2015

Version number 5

Revision: 14.05.2015

#### Trade name: Nullifire SC900 Repair A

(Contd. of page 4)

be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties				
· General Information				
· Appearance:				
Form:	Viscous			
Colour:	White			
· Odour:	Characteristic			
<ul> <li>Boiling point/Boiling range:</li> </ul>	> 100 °C			
· Flash point:	46 °C			
· Ignition temperature:	500 °C			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.			
· Density at 20 °C:	1.55 g/cm <sup>3</sup>			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			
· Solvent content:				
VOC (EC)	139 g/l			
9.2 Other information	No further relevant information available.			

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- 10.4 Conditions to avoid
  - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - $\cdot$  10.5 Incompatible materials: No further relevant information available.
  - **10.6 Hazardous decomposition products:** Nitrogen oxides

Carbon monoxide and carbon dioxide

(Contd. on page 6)



Printing date 14.05.2015

Version number 5

Revision: 14.05.2015

Trade name: Nullifire SC900 Repair A

(Contd. of page 5)

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

#### 1330-20-7 xylene (mix)

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

### · Primary irritant effect:

· Skin corrosion/irritation Slight irritation possible

- · Serious eye damage/irritation Slight irritation possible.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information: Repeated exposure may cause skin dryness or cracking.

# **SECTION 12: Ecological information**

· 12.1 Toxicity

Aquatic toxicity:

1330-20-7 xylene (mix)

EC50/48 h 7.4 mg/L (daphnia magna)

EC50/72 h 10 mg/L (skelettonema costatum)

LC50/96 h 3.77 mg/L (fish)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes: Overall evaluation Avoid transfer into the environment.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

• Waste disposal key: UK : H3B

# · European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

(Contd. on page 7)



Revision: 14.05.2015

Printing date 14.05.2015

Version number 5

Trade name: Nullifire SC900 Repair A

(Contd. of page 6)

#### · Uncleaned packaging:

# · Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Non contaminated packagings may be recycled.

SECTION 14: Transport informatio	n
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
<ul> <li>· 14.2 UN proper shipping name</li> <li>· ADR, ADN, IMDG, IATA</li> </ul>	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
<ul> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	No
· 14.6 Special precautions for user	Not applicable.
<ul> <li>• 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code</li> </ul>	ex II of Not applicable.
· Transport/Additional information:	
· ADR	2.2.3.1.1 (note 1) 2.2.3.1.5
·IMDG	2.3.1.2 + 2.3.1.3 2.3.2.5
· IATA	3.3.1.2 + 3.3.1.3
· UN "Model Regulation":	UN-, -

# **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/45/EC. "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1). "CHIP" SI 2009 No.716. "REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

· National regulations:

· Other regulations, limitations and prohibitive regulations

• Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.

(Contd. on page 8)

GB



Printing date 14.05.2015

Version number 5

Revision: 14.05.2015

Trade name: Nullifire SC900 Repair A

(Contd. of page 7)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.

#### R10 Flammable.

- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R38 Irritating to skin.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

 $\cdot$  \* Data compared to the previous version altered.

GB